

UCL2 1200x215 41W

SURFACE MOUNTED LUMINAIRE



NL-D-1200x215-41W-xx-z

PRODUCT SPECIFICATIONS

Product code	NL-D-1200x215-41W-xx-z
Voltage	220 V - 240 V
System power	41 W
Frequency	50–60 Hz
Power factor (PF)	0,95
LED type	AS-5630WxA2-C2C065-0101-YCx-LTH
Number of LEDs	128 pcs
Beam angle	120°
Dimensions	1200 mm × 215 mm × 55 mm
Weight	5,2 kg
Protection	IP20
Operating temperature (tc)	-20° C – +68° C
Ambient temperature (ta)	-20° C – +45° C
Lifetime (L70)	80 000 h
Color rendering index	Ra>80
Housing color	grey



MADE IN EU

DALI

CLO

TOUCH
DIM



PRODUCT FEATURES

The UCL2 lighting series has an elegant design and is therefore suitable for modern offices and commercial spaces. The DALI version enables different control methods.

order no.	product code	diffuser	CCT	luminous flux
52291-xx	NL-D-1200x215-41W-xx-m	milky	xx ...	6 000 lm
52294-xx	NL-D-1200x215-41W-xx-p	prismatic	WD for 5000K, WN for 4000K, WW for 3000K	5 170 lm
52297-xx	NL-D-1200x215-41W-xx-w	white		5 170 lm
52591-xx	NL-D-1200x215-41W-xx-m-D DALI	milky		6 000 lm
52594-xx	NL-D-1200x215-41W-xx-p-D DALI	prismatic	lumen output with 3000K approx. 10% lower	5 170 lm
52597-xx	NL-D-1200x215-41W-xx-w-D DALI	white		5 170 lm