

UCL2 600x600 37W

SURFACE MOUNTED LUMINAIRE



NL-D-600x600-37W-xx-z

PRODUCT SPECIFICATIONS

Product code	NL-D-600x600-37W-xx-z
Voltage	220 V - 240 V
System power	37 W
Power supply unit	OSRAM OT FIT 55/220-240/1A0 CS L
Frequency	50–60 Hz
Power factor (PF)	0,95
LED type	AS-5630WxA2-C2C065-0101-YCx-LTH
Number of LEDs	126 pcs
Beam angle	120°
Dimensions	600 mm × 600 mm × 55 mm
Weight	6,2 kg
Protection	IP20
Operating temperature (tc)	-20° C – +68° C
Ambient temperature (ta)	-20° C – +45° C
Lifetime (L70)	90 000 h
Color rendering index	Ra>80
Housing color	grey



MADE IN EU

DALI

CLO

TOUCH
DIM

EMERG.

IP20



PRODUCT FEATURES

The UCL2 lighting series has an elegant design and is therefore suitable for modern offices and commercial spaces. The DALI version enables different control methods. The luminaire can be equipped with an emergency module.

order no.	product code	diffuser	CCT	luminous flux
52271-xx	NL-D-600x600-37W-xx-m	milky	xx ...	5 420 lm
52274-xx	NL-D-600x600-37W-xx-p	prismatic	WD for 5000K, WN for 4000K, WW for 3000K	4 670 lm
52277-xx	NL-D-600x600-37W-xx-w	white		4 670 lm
52571-xx	NL-D-600x600-37W-xx-m-D DALI	milky		5 420 lm
52574-xx	NL-D-600x600-37W-xx-p-D DALI	prismatic	lumen output with 3000K approx. 10% lower	4 670 lm
52577-xx	NL-D-600x600-37W-xx-w-D DALI	white		4 670 lm