

# UCL2 600x600 48W

## SURFACE MOUNTED LUMINAIRE



## NL-D-600x600-48W-xx-z

### PRODUCT SPECIFICATIONS

Product code	NL-D-600x600-48W-xx-z
Voltage	220 V - 240 V
System power	48 W
Power supply unit	OSRAM OT FIT 55/220-240/1A0 CS L
Frequency	50–60 Hz
Power factor (PF)	0,95
LED type	AS-5630WxA2-C2C065-0101-YCx-LTH
Number of LEDs	126 pcs
Beam angle	120°
Dimensions	600 mm × 600 mm × 55 mm
Weight	6,2 kg
Protection	IP20
Operating temperature (tc)	-20° C – +68° C
Ambient temperature (ta)	-20° C – +45° C
Lifetime (L70)	70 000 h
Color rendering index	Ra>80
Housing color	grey



MADE IN EU

DALI

CLO

TOUCH  
DIM

EMERG.

IP20



### PRODUCT FEATURES

The UCL2 lighting series has an elegant design and is therefore suitable for modern offices and commercial spaces. The DALI version enables different control methods. The luminaire can be equipped with an emergency module.

order no.	product code	diffuser	CCT	luminous flux
52273-xx	NL-D-600x600-48W-xx-m	milky	xx ...	6 910 lm
52276-xx	NL-D-600x600-48W-xx-p	prismatic	WD for 5000K, WN for 4000K, WW for 3000K	5 960 lm
52279-xx	NL-D-600x600-48W-xx-w	white		5 960 lm
52573-xx	NL-D-600x600-48W-xx-m-D DALI	milky		6 910 lm
52576-xx	NL-D-600x600-48W-xx-p-D DALI	prismatic	lumen output with 3000K approx. 10% lower	5 960 lm
52579-xx	NL-D-600x600-48W-xx-w-D DALI	white		5 960 lm