

NL-ECL-540×260-45W-xx

PRODUCT SPECIFICATIONS

Product code	NL-ECL-540×260-45W-xx
Voltage	220 V - 240 V
LED driver	OSRAM OT40/120-277/1A04DIMLT2E
System power	45 W
Frequency	50–60 Hz
Power factor (PF)	0,95
LED type	Alder AS-5258WxA2-C2C210-0303
Number of LEDs	24 pcs
Beam angle	150°/65°
PCB material	aluminum
Dimensions	540 mm × 260 mm × 185 mm
Weight	4,8 kg
Protection	IP65
Operating temperature (tc)	-30° C – +75° C
Ambient temperature (ta)	-30° C – +50° C
Lifetime (L70)	min. 70 000 h
Color rendering index	Ra>80
Housing color	grey
	<u> </u>





MADE IN EU

IP65	

IK08

DALI

CLO

ASTRO DIM MAINS DIM STEP DIM





LED driver is separated from LED module



Adjustable tilt angle



COLOR TEMPERATURE AND LUMINOUS FLUX

order no.	product code	color temperature	ССТ	luminous flux
51770-65	NL-ECL-540x260-45W-WC	cold white	6 500 K	6 010 lm
51770-50	NL-ECL-540x260-45W-WD	daylight white	5 000 K	6 010 lm
51770-40	NL-ECL-540x260-45W-WN	normal white	4 000 K	6 010 lm
51770-30	NL-ECL-540x260-45W-WW	warm white	3 000 K	5 430 lm

PRODUCT FEATURES


The Ecoline 45W, manufactured with the latest Alder LED technology, is designed for outdoor lighting of roads, car parks and buildings.

The Ecoline Series is equipped with the AstroDIM feature, which allows additional energy savings in twilight phases. Furthermore, MainsDIM for dimming via reduction of line voltage amplitude and DALI for intelligent light management. A constant luminous flux can be set by using the CLO function.

The luminaire has an integrated surge protection and it is suitable for poles with a diameter of max 60mm.



Uniform light distribution by using asymmetric optics



Similar products: Ecoline 60W

order no.	product code	color temperature	ССТ	luminous flux
51765-65	NL-ECL-540x260-60W-WC	cold white	6 500 K	8 180 lm
51765-50	NL-ECL-540x260-60W-WD	daylight white	5 000 K	8 180 lm
51765-40	NL-ECL-540x260-60W-WN	normal white	4 000 K	8 180 lm
51765-30	NL-ECL-540x260-60W-WW	warm white	3 000 K	7 370 lm