

TPL 1200 55W

LINEAR LUMINAIRE



NL-TPL-1200x80-55W-xx-z

PRODUCT SPECIFICATIONS

Product code	NL-TPL-1200x80-55W-xx-z
Voltage	220 V - 240 V
LED driver	OSRAM OT FIT 55/220-240/1A0 CS L
System power	55 W
Frequency	50–60 Hz
Power factor (PF)	0,98
LED type	AS-5630WxA2-C2C065-0101-YCx-LTH
Number of LEDs	128 pcs
Beam angle	120°
PCB material	aluminum
Dimensions	1200mm x 80mm x 77mm
Weight	2,7 kg
Protection	IP65
Operating temperature (tc)	-20° C – +68° C
Ambient temperature (ta)	-20° C – +45° C
Lifetime (L70)	min. 70 000 h
Color rendering index	Ra > 80



MADE IN EU

IP65

DALI


TOUCH
DIM

CLO

IK08

EMERG.

120°



A high-quality aluminium body provides excellent heat dissipation.



TPL 1200 55W

LINEAR LUMINAIRE



PRODUCT FEATURES

Quality and versatile linear TPL luminaires are particularly suitable for lighting in industry systems, corridors and workshops. The high IP code protects the luminaire from dust particles and adverse the effects of industrial environments.

The aluminum body ensures optimum heat dissipation. The light fixture can be mounted with brackets directly to the ceiling or as a pendant luminaire.

TPL luminaires come with a milky diffuser as standard. A clear diffuser can be used for higher ceilings. The fixture can be equipped with an emergency module or DALI.



COLOR TEMPERATURE AND LUMINOUS FLUX

order no.	product code	diffuser / version	CCT	color temperature	luminous flux
51976-50	NL-TPL-1200x80-55W-WD-m	milky / standard	5 000 K	daylight white	7 580 lm
51976-40	NL-TPL-1200x80-55W-WN-m	milky / standard	4 000 K	normal white	7 580 lm
51976-30	NL-TPL-1200x80-55W-WW-m	milky / standard	3 000 K	warm white	6 820 lm
51979-50	NL-TPL-1200x80-55W-WD-c	clear / standard	5 000 K	daylight white	8 020 lm
51979-40	NL-TPL-1200x80-55W-WN-c	clear / standard	4 000 K	normal white	8 020 lm
51979-30	NL-TPL-1200x80-55W-WW-c	clear / standard	3 000 K	warm white	7 220 lm
51996-50	NL-TPL-1200x80-55W-WD-m-D	milky / DALI	5 000 K	daylight white	7 580 lm
51996-40	NL-TPL-1200x80-55W-WN-m-D	milky / DALI	4 000 K	normal white	7 580 lm
51996-30	NL-TPL-1200x80-55W-WW-m-D	milky / DALI	3 000 K	warm white	6 820 lm
51999-50	NL-TPL-1200x80-55W-WD-c-D	clear / DALI	5 000 K	daylight white	8 020 lm
51999-40	NL-TPL-1200x80-55W-WN-c-D	clear / DALI	4 000 K	normal white	8 020 lm
51999-30	NL-TPL-1200x80-55W-WW-c-D	clear / DALI	3 000 K	warm white	7 220 lm
51970-50	NL-TPL-1200x80-55W-WD-m-N	milky / emergency	5 000 K	daylight white	7 580 lm
51970-40	NL-TPL-1200x80-55W-WN-m-N	milky / emergency	4 000 K	normal white	7 580 lm
51970-30	NL-TPL-1200x80-55W-WW-m-N	milky / emergency	3 000 K	warm white	6 820 lm
51973-50	NL-TPL-1200x80-55W-WD-c-N	clear / emergency	5 000 K	daylight white	8 020 lm
51973-40	NL-TPL-1200x80-55W-WN-c-N	clear / emergency	4 000 K	normal white	8 020 lm
51973-30	NL-TPL-1200x80-55W-WW-c-N	clear / emergency	3 000 K	warm white	7 220 lm
52496-50	NL-TPL-1200x80-55W-WD-m-D-N	milky / DALI / emerg.	5 000 K	daylight white	7 580 lm
52496-40	NL-TPL-1200x80-55W-WN-m-D-N	milky / DALI / emerg.	4 000 K	normal white	7 580 lm
52496-30	NL-TPL-1200x80-55W-WW-m-D-N	milky / DALI / emerg.	3 000 K	warm white	6 820 lm
52499-50	NL-TPL-1200x80-55W-WD-c-D-N	clear / DALI / emerg.	5 000 K	daylight white	8 020 lm
52499-40	NL-TPL-1200x80-55W-WN-c-D-N	clear / DALI / emerg.	4 000 K	normal white	8 020 lm
52499-30	NL-TPL-1200x80-55W-WW-c-D-N	clear / DALI / emerg.	3 000 K	warm white	7 220 lm