

TPL 635 26W

LINEAR LUMINAIRE



NL-TPL-635x80-26W-xx-z

PRODUCT SPECIFICATIONS

Product code	NL-TPL-635x80-26W-xx-z
Voltage	220 V - 240 V
LED driver	OSRAM OT FIT 35/220-240/700 CS L G2
System power	26 W
Frequency	50–60 Hz
Power factor (PF)	0,98
LED type	AS-5630WxA2-C2C065-0101-YCx-LTH
Number of LEDs	64 pcs
Beam angle	120°
PCB material	aluminum
Dimensions	635mm x 80mm x 77mm
Weight	1,6 kg
Protection	IP65
Operating temperature (tc)	-20° C – +68° C
Ambient temperature (ta)	-20° C – +45° C
Lifetime (L70)	min. 70 000 h
Color rendering index	Ra > 80



MADE IN EU

IP65


DALI

TOUCH
DIM

IK08



CLO



A high-quality aluminium body provides excellent heat dissipation.



TPL 635 26W

LINEAR LUMINAIRE




PRODUCT FEATURES

Quality and versatile linear TPL luminaires are particularly suitable for lighting in industry systems, corridors and workshops. The high IP code protects the luminaire from dust particles and adverse the effects of industrial environments.

The aluminum body ensures optimum heat dissipation. The light fixture can be mounted with brackets directly to the ceiling or as a pendant luminaire.

TPL luminaires come with a milky diffuser as standard. A clear diffuser can be used for higher ceilings. The fixture can be equipped with DALI.



COLOR TEMPERATURE AND LUMINOUS FLUX

order no.	product code	diffuser / version	CCT	color temperature	luminous flux
52451-50	NL-TPL-635x80-26W-WD-m	milky / standard	5 000 K	daylight white	3 590 lm
52451-40	NL-TPL-635x80-26W-WN-m	milky / standard	4 000 K	normal white	3 590 lm
52451-30	NL-TPL-635x80-26W-WW-m	milky / standard	3 000 K	warm white	3 230 lm
52452-50	NL-TPL-635x80-26W-WD-c	clear / standard	5 000 K	daylight white	3 790 lm
52452-40	NL-TPL-635x80-26W-WN-c	clear / standard	4 000 K	normal white	3 790 lm
52452-30	NL-TPL-635x80-26W-WW-c	clear / standard	3 000 K	warm white	3 450 lm
52453-50	NL-TPL-635x80-26W-WD-m-D	milky / DALI	5 000 K	daylight white	3 590 lm
52453-40	NL-TPL-635x80-26W-WN-m-D	milky / DALI	4 000 K	normal white	3 590 lm
52453-30	NL-TPL-635x80-26W-WW-m-D	milky / DALI	3 000 K	warm white	3 230 lm
52454-50	NL-TPL-635x80-26W-WD-c-D	clear / DALI	5 000 K	daylight white	3 790 lm
52454-40	NL-TPL-635x80-26W-WN-c-D	clear / DALI	4 000 K	normal white	3 790 lm
52454-30	NL-TPL-635x80-26W-WW-c-D	clear / DALI	3 000 K	warm white	3 450 lm