

GCL7 595x595 42W

GRID CEILING LIGHT



NL-V7-595x595-42W-xx-z

PRODUCT SPECIFICATIONS

Product code	NL-V7-595X595-42W-xx-z
Voltage	220 V - 240 V
LED driver	OSRAM OT FIT 55/220-240/1A0 CS L
System power	42 W
Frequency	50–60 Hz
Power factor (PF)	0,95
LED type	AS-5630WxA2-C2C065-0101-YCx-LTH
Number of LEDs	126 pcs
Beam angle	120°
Dimensions	595 mm × 595 mm × 75 mm
Weight	4,3 kg
Protection	IP65
Operating temperature (tc)	-20° C – +68° C
Ambient temperature (ta)	-20° C – +45° C
Lifetime (L70)	80 000 h
Color rendering index	Ra>80



MADE IN EU

IP65

DALI

CLO

TOUCH
DIM

EMERG.



PRODUCT FEATURES

The luminaire is suitable for mineral fibre ceilings with a 600mm grid and is typical for office and commercial lighting. GCL luminaires are also available for plasterboard ceilings as PCL luminaires.

IP65 ensures the luminaire is protected from dust and dirt and makes it maintenance-free.

The fixture can be equipped with an emergency module or DALI.

order no.	product code	diffuser	CCT	luminous flux
52202-xx	NL-V7-595x595-42W-xx-m	milky	xx ...	6 150 lm
52222-xx	NL-V7-595x595-42W-xx-w	white		5 300 lm
52212-xx	NL-V7-595x595-42W-xx-m-D DALI	milky	WD for 5000K, WN for 4000K, WW for 3000K	6 150 lm
52232-xx	NL-V7-595x595-42W-xx-w-D DALI	white		5 300 lm
52202-xxN	NL-V7-595x595-42W-xx-m-N	milky	luminous flux is 10% lower for 3000K	6 150 lm
52222-xxN	NL-V7-595x595-42W-xx-w-N	white		5 300 lm
52212-xxN	NL-V7-595x595-42W-xx-m-D-N DALI	milky	N... emergency module	6 150 lm
52232-xxN	NL-V7-595x595-42W-xx-w-D-N DALI	white		5 300 lm